

Network Speed Dome Camera da esterno // 2.1 Mp // 0 Lux // Focale 5.5 - 110 mm. // 10 LED Array - portata 120 mt. // ONVIF // Motion Detection // 25Fps // Zoom 20x




Caratteristiche

- CCD: 2.1 Megapixel CMOS
- LENTE: 5.5 - 110 mm.
- FILTRO ELETTRONICO
- FORMATO: H.264
- FRAME: 25 in Full HD (1920 x 1080)
- NUMERO LED: 10 LED IR Array con portata 120 mt.
- ACCESSO: tramite Internet Explorer (Web server integrato)
- ALIMENTAZIONE: 12Vdc, 4 A
- DIMENSIONI: 228 Ø x 399 mm.
- IP 66

Specifiche ATVIPSD31W-IR

Sensore	2.1 Mp CMOS Sensor
Segnale	NTSC, PAL
Pixel Effettivi	1920 x 1080
SNR	≥50dB (AGC Off)
Minima Illuminazione	0 Lux / F1.4
Operating System	Embedded Linux
Video Compression Standard	H.264
Video Bitrate	32 Kbps - 8 Mbps settable
Frame Rate	50 Hz. : 25 fps (1920 x 1080) 60 Hz. : 30 fps (1920 x 1080)
Smart Alarm	Motion detection, Broken cable, IP address conflict
Protocolli supportati	TCP/IP, UDP, IGMP, DHCP, HTTP, HTTPS, DNS, DDNS, RTP/RTSP, PPPoE, SMTP, UPnP, NTP, ARP, ONVIF/PSIA
Zoom	20 x
Image settings	Saturation, brightness, contrast can be adjusted by client and IE browser
Day & Night	Filtro elettronico
Obiettivo	5.5 - 110 mm.
IR LED	10 pcs IR Array LEDS
Portata LED	120 mt.
Tensione IN	DC 12V ± 10%
Corrente	4 A
Potenza di consumo	<26W
Peso	6,5 Kg.
Grado di protezione IP	IP66
Temperatura di esercizio	-40°C +70°C
Grado di umidità	<95% RH (no condensazione)

Dimensioni:



CODICE	DESCRIZIONE	
ATVIPSD31W-IR	Network Speed Dome Camera da esterno // 2.1 Mp // Day & night 0 Lux // Filtro elettronico // Focale 5.5 - 110 mm. // 10 LED Array portata 120 mt. // ONVIF // Motion Detection // 25Fps Full HD	